EC315689655IN IVR:6967315689655

SP BILASPUR KUTCHERY BILASPURCSHSD
Counter No:1,26/12/2024,12:56

To:C.G. ENVIRONM..
PIN:492002, Mantralaya Raipur SO
From:DELHI MSW SOLUTION LTD ..

Wt:165gms
Amt:41.30,Tax:6.30,Amt.Paid:41.00(Cash)

(Track on www.indiapost.gov.in)

(Dial 10002666868) (Wear Masks, Stay Safe)

भारतीय डाक

SP BILASPUR KUTCHERY BILASPURCUMES (49500)
Counter No:1,26/12/2024,12:56
To:SETAA C.B. PARYAVAS BHAWAN. India Post
PIN:492002, Mantralaya Raipur SD
From:DELHI MSW SOLUTION LTD ...
Wt:165cms
Amt:41.30,Tax:6.30,Amt.Paid:41.00(Cash)
<Track on www.indiapost.gov.in>
<Dial 1800266668> (Wear Masks, Stay Safe)

EC315689633IN IVR:696731568963URCRISIO

EP BILASPUR KUTCHERY BILASPURGES

Counter No:1,26/12/2024,12:56

fo:THE ADDITIONAL PCCF,. India Post

PIN:440001, Nagour GPO

From:DELHI MSW SULUTION LTD ,.

Wt:165yms

Amt:47.20,Tax:7.20,Amt.Paid:47.00(Cash)

(Track on www.indiapost.gov.in)

(Dial 18002666888) (Wear Masks, Stay Safe)

EC315689664IN IVR:6967315689664TPU SICO
SP BILASPUR KUTCHERY BILASPURGE (495641)
Counter No:1,26/12/2024,12:34
To:REGIONAL OFFI..
PIN:495001, Bilaspur Kutchery BilaspurCoHso
From:DELHI MSW SOLUTION LTD ..
Wt:165qms
Amt:29.50.Tax:4.50.Amt.Paid:30.00(Cash)
<Track on www.indiapost.gov.in
<Dial 16002666868) (Wear Masks, Stay Safe)







DELHI MSW SOLUTIONS LTD.
(A Re Sustainability Ltd. Venture)
CIN: U90001 TG2009PLC063708
H. No: 259/1/ Lane No. R-04,
Mahamaya Vihar, Ware House Road,

Bilaspur, Chattisgarh - 495001 www.delhimswsolutions.com

Ref No: DMSW/ISWM/BILASPUR/176/2024-25

Date: 25.12.2024

To

The Additional PCCF (Central West Zone)
Ministry of Environment, Forest and Climate Change,
Regional Office (WCZ), Ground Floor, East Wing,
New Secretariat Building Civil Lines, Nagpur-440001

Sub: Submission of six-monthly environmental clearance compliance report for the integrated solid waste management plant in Kachhar village.

Dear Sir,

With reference to the above subject, please find here with six monthly compliance status report for the period of April 2024 to September 2024 for the integrated solid waste management plant in Village-Kachhar, Post-Sendri, and Bilaspur-495009 (C.G.)

Thanking You,

Yours Sincerely,

For Delhi MSW Solutions Limited

Prana Ranjan

Plant Head

Encl: As Above

Copy to:

- SEIAA CHHATTISGARH, PARYAVAS BHAWAN, NORTH BLOCK, SECT-19, NAVA RAIPUR ATAL NAGAR, DIST. - RAIPUR (C.G.) 492002
- CHHATTISGARH ENVIRONMENT CONSERVATION BOARD PARYAVAS BHAWAN, NORTH BLOCK, SECTOR -19, NAVA RAIPUR ATAL NAGAR, RAIPUR (C.G.) 492002
- 3. REGIONAL OFFICE CHHATTISGARH ENVIRONMENT CONSERVATION BOARD VYAPAR VIHAR NEAR PT. DINDAYAL UPADYAY GARDEN DIST: BILASPUR (C.G.)





HALF YEARLY COMPLIANCE REPORT (April to September) 2024

DELHI MSW SOLUTIONS LIMITED
(INTEGRATED WASTE MANAGEMENT PLANT)





Serial No.	EC COMPLIANCE POINT WISE	COMPLIANCE STATUS REPORT
1	Total land for proposed common municipal solid waste management facility shall not exceed 25 acres.	Total land proposed for common municipal solid waste management facility has not been exceeded 25 acres.
2	The common municipal solid waste management facility shall be set up as per the guidelines of the ministry of urban development, Government of India and CPCB, Delhi.	The common municipal solid waste management facility in Bilaspur has already been set up as per the guidelines of the ministry of urban development, Government of India and CPCB, Delhi. Please refer to the attached ANNEXURE –I.
3	The 'landfill cells' shall be developed in a phased manner to avoid water logging and misuse. The establishment of solid waste management facility shall comply the criteria laid down in Solid Waste Management Rule, 2016.	We have four landfill cells proposed for the project of the 15 years. The landfill cells have been developed in phased manner to avoid water logging and misuse. Currently cell B is in operation after successful construction and cell A is full that complies the criteria laid down in Solid Waste Management Rule, 2016. Photos of existing landfill and proposed are attached in the ANNEXURE -II .
4	Project proponent shall obtain no objection certificate from the Civil Aviation Authority/Airport Authority (as the case may be) before commencement of any activity on the site.	Project proponent has already obtained the no objection certificate from the Civil Aviation Authority/Airport Authority. The Proof of Airport NOC has been attached in the ANNEXURE -III.
5	The site for landfill, processing and disposal of solid wastes shall be incorporated in the Town Planning Department's land-use plan.	The facility area for landfill, processing and disposal of solid wastes has already been incorporated in the Town Planning Department's land-use plan. Details has been attached in ANNEXURE -IV.
6	A minimum 100-meter buffer zone of no development shall be maintained around solid waste processing and disposal facility.	Being Complied. We have already maintained 500-meter buffer zone of no development in our solid waste processing & disposal facility area. Details has been attached in ANNEXURE - V.
7	The biomedical wastes shall be disposed of in accordance with the Biomedical Waste Management Rules, 2016 as amended from time to time. The hazardous waste shall be managed in accordance with the Hazardous and Other Waste (Management and Tran's boundary Movement) Rules, 2016, as amended from time to time. The E- Waste shall be managed in accordance with the E-Waste (Management) Rules, 2016 as amended from time to time.	We do not deal with any kind of bio medical and e waste. Hazardous waste like waste oil that is generated in the plant premises, reused for oiling and maintenance purposes of the machineries present in the plant. Used batteries are send to the vendor and replaced with new one.





8	Temporary storage facility for municipal solid wastes shall be established in site to accommodate the waste in case of non-operation of waste processing and during emergency or natural calamities.	Temporary storage facility for municipal solid wastes is established in site to accommodate the waste in case of non-operation of waste processing and during emergency or natural calamities up to seven days.
9	Fossil fuel such as coal, furnace oil, wood shall not be utilized / burnt in the proposed RDF plant at Kacchar for drying. Project proponent shall utilize fly ash bricks/blocks etc. in all construction activities.	Burning of any kind of waste doesn't take place in the proposed RDF plant at Kacchar for drying. Fly ash bricks / blocks are used in construction activities while required.
10	Site shall be fenced / separated by boundary wall from adjoining area and provided with proper gate to monitor incoming vehicles, to prevent entry of unauthorized persons and stray animals. Project proponent shall ensure transportation of solid wastes to the site only after completing the fencing / boundary wall along with gate and plantation.	Site is separated by boundary wall from adjoining area and proper gate is present to monitor incoming vehicle. Proper security is maintained to prevent entry of unauthorized persons and stray animals. Transportation of solid waste is only carried out inside the boundary wall along with gate and plantation. Proof of the compliance has been attached in ANNEXURE VI.
11	The approach and / internal roads shall be concreted or paved so as to avoid generation of dust particles due to vehicular movement and shall be so designed to ensure free movement of vehicles and other machinery.	The approach road and internal roads are concreted to avoid generation of dust particles caused by vehicle movement and its 5.5 meter wide to ensure free movement of vehicles and other machinery.
12	The site shall have waste inspection facility to monitor waste brought in for processing, office facility for record keeping and shelter for keeping equipment and machinery including pollution monitoring equipment. The operator of the facility shall maintain record of waste receive, processed and disposed.	Waste is sent for processing only after proper inspection. Office facility for mentioned purposes are available. We have Store room and in house laboratory for the shelter for keeping equipment and machinery including pollution monitoring equipment's respectively. Waste received, processed and disposed are recorded through online integrated centralized weighbridge software along with separate excel sheet in a particular system. Daily record keeping in logbook is also carried out on a regular basis.
13	Provisions like weigh bridge to measure quantity of waste brought at site, fire protection equipment and other facilities as may be required shall be provided.	Weighbridge to measure the weight of incoming waste, fire extinguishers, fire hydrant lines for firefighting and other facilities are provided.
14	Utilities such as drinking water and sanitary facilities (preferably washing / bathing facilities for workers) and lighting arrangements for shall be provided.	Separate sanitary facilities for washing and bathing for workers are provided. Drinking water facilities is provided by a separate tank of drinking water and lighting arrangements in and around the plant premises is maintained. Proof of the given compliance has been attached in the ANNEXURE -VII.
15	Safety provisions including health inspections of workers at landfill site shall be provided.	Provisions for all kind of safety for the workers is maintained in the premises by the safety officer of the site. Health inspection is being





		complied, and it is carried out once in a every
		year.
16	Provisions for parking, cleaning, washing of transport vehicles carrying solid waste shall be provided. The wastewater so generated shall be treated to meet the prescribed standards. Treated effluent shall be used for plantation within premises. Adequate facility for proper treatment of industrial (if any) and domestic effluent shall be provided to ensure the treated effluent quality within standard prescribed by Ministry of Environment. Forest and Climate Change, Government of India. Any liquid effluent what so ever generated from industrial (if any) and domestic activities shall not be discharged into the river or any surface water bodies under any circumstances, and it shall be reused wholly in the process/plantation. Project authority shall provide sewage treatment system of adequate capacity for treatment of domestic effluent generated.	Provision for parking, cleaning, and washing of transport vehicles is provided. Waste water generated is treated with the help of Multi Effective Evaporator to meet the prescribed standards and treated effluent is used for watering the plantation around the plant premises. Any liquid effluent what so ever generated from industrial (if any) and domestic activities is not discharged into the river or any surface water bodies under any circumstances, and it shall be reused wholly in the process/plantation. Details has been shown in ANNEXURE VIII
17	Waste shall be compacted in thin layers using heavy compactors to achieve high density of the waste. In heavy rainfall situation, when heavy compactors cannot be used, alternative measures shall be adopted.	Waste is compacted in thin layers using heavy compactors
18	Till the time waste processing facilities for composting or recycle are set up, the waste shall be sent to the sanitary landfill. The landfill shall be covered at the end of each working day with minimum 10 cm of soil, inert debris or construction material.	Waste was sent to the landfill at the time of setting up of the waste processing facility and landfill is regularly covered within 15c.m soil or inert.
19	Prior to the commencement of monsoon season, an intermediate cover of 40-65 cm thickness of soil shall be placed on the landfill with proper compaction and grading to prevent infiltration during monsoon. Proper drainage shall be constructed to divert run-off away from the active cell of the landfill.	Prior to the commencement of monsoon season, an intermediate cover of 60c.m cm thickness of soil on the landfill is given and also tarpaulin cover is given to prevent infiltration. Drainage is constructed to divert run-off away from the active cell of the landfill.





	,	
20	After completion of landfill, a final cover shall be designed to minimise infiltration and erosion. The final cover shall meet the following specifications, namely: a. The final cover shall have a barrier soil layer comprising of 60 cm of clay or amended soil with permeability coefficient less than 1 x 10-7 cm/sec. b. On top of the barrier soil layer, there shall be a drainage layer of 15 cm. c. On top of the drainage layer, there shall be a vegetative layer of 45 cm to support natural plant growth and to minimise erosion.	After completion of landfill, a final cover has already been done to minimise infiltration for Cell -A, Cell B is in still operation phase. No operation has been started yet for Cell C & D.
21	The storm water drain shall be designed and constructed in such a way that the surface runoff water is diverted from the landfilling site and leachates from solid waste locations do not get mixed with the surface runoff water. Provisions for diversion of storm water discharge drains shall be made to minimise leachate generation and prevent pollution of surface water and also for avoiding flooding and creation of marshy conditions.	The storm water drain has already been built and configured so that surface runoff water is routed away from the landfilling site and that leachates from solid waste locations are not mixed together. Storm water discharge drains have been diverted in order to reduce leachate production, prevent surface water contamination, prevent floods, and prevent the development of marshy conditions.
22	Non-permeable lining system at the base and walls of waste disposal area shall be provided. For landfill receiving residues of waste processing facilities or mixed waste or waste having contamination of hazardous materials (such as aerosols, bleaches, polishes, batteries, waste oils, paint products and pesticides) shall have liner of composite barrier of 1.5 mm thick high density polyethylene (HDPE) geo-membrane or geo-synthetic liners, or equivalent, overlying 90 cm of soil (clay or amended soil) having permeability coefficient not greater than 1 x 10-7 cm/sec. The highest level of water table shall be at least two meters below the base of clay or amended soil barrier layer provided at the bottom of landfills.	Non-permeable HDPE lining system at the base and walls of waste disposal area has already been provided. For landfill receiving residues of waste processing facilities or mixed waste or waste having contamination of hazardous materials (such as aerosols, bleaches, polishes, batteries, waste oils, paint products and pesticides) is having liner of composite barrier of 1.5 mm thick high density polyethylene (HDPE) geo-membrane or geosynthetic liners, or equivalent, overlying 90 cm of soil (clay or amended soil) having permeability coefficient not greater than 1 x 10-7 cm/sec. The highest level of water table is 20 meters below the base of clay or amended soil barrier layer provided at the bottom of landfills.
23	Provisions for management of leachates including its collection and treatment shall be made. The treated leachate shall be recycled or utilized within premises. In no case, leachate shall be released into open environment.	In our facility area we have separate provision for leachate treatment





24	Arrangement shall be made to prevent leachate runoff from landfill area entering any drain, stream, river, lake or pond. In case of mixing of runoff water with leachate or solid waste, the entire mixed water shall be treated by the project proponent.	We have arrangements to collect leachate in a leachate collection tank with the help of grid pipes and spread in the landfill. Thus, we prevent leachate runoff from landfill area entering any drain, stream, river, lake or pond.
25	Baseline data of ground water quality in the area shall be collected and kept in record for future reference by Project proponent. The ground water quality within 50 meters of the periphery of site shall be periodically monitored covering different seasons in a year that is, summer, monsoon and post-monsoon period to ensure that the ground water is not contaminated. Ground water quality monitoring in nearby villages shall be done on regular basis.	Ground water quality monitoring and reporting is conducted by a NABL certified lab within 50 meters of the periphery of site on periodic basis covering different seasons in a year that is, summer, monsoon and postmonsoon period to ensure that the ground water is not contaminated. We collected the baseline data at the time of construction of the plant and kept in record for future reference. Details has been shown in ANNEXURE IX
26	Usage of ground water in and around the site for any purpose (including drinking and irrigation) shall be considered only after ensuring its quality.	Ground water in and around the site for any purpose (including drinking and irrigation) is used only after ensuring the quality test from N.A.B.L certified lab. Test reports are attached as supporting document. ANNEXURE X
27	Landfill gas control system including gas collection system shall be installed at landfill site to minimize odour, prevent off-site migration of gases, to protect vegetation planted on the rehabilitated landfill surface etc. For enhancing landfill gas recovery, use of geomembranes in cover systems along with gas collection wells should be considered.	We will comply after the completion of landfill.
28	The concentration of methane gas generated at landfill site shall not exceed 25 per cent of the lower explosive limit (LEL).	We have conducted air monitoring from NABL certified lab which shows that the concentration of methane gas generated at landfill site does not exceed 25 per cent of the lower explosive limit [LEL]. File of air monitoring is kept in record on periodic basis. Details has been shown in ANNEXURE XI
29	The landfill gas from the collection facility at a landfill site shall be utilized for either direct thermal applications or power generation, as per viability. Otherwise, landfill gas shall be burnt (flared) and shall not be allowed to escape directly to the atmosphere or for illegal tapping. Passive venting shall be allowed in case if its utilization or flaring is not possible.	We comply it in post closure period.
30	Ambient air quality at the landfill site and at the vicinity shall be regularly monitored. Ambient air quality shall meet the standards prescribed in this regard.	We have tested the ambient air quality at the landfill site and at the vicinity area on three points at angle 120 degree apart to the landfill and the ambient air quality meets the standards prescribed in this regard. Test reports are kept in record on periodic basis.





		Periodic monitoring report of ambient air quality monitoring has been attached in ANNEXURE XII
31	A vegetative cover shall be provided over the completed site in accordance with the following specifications, namely: - a. Locally adopted non-edible perennial plants that are resistant to drought and extreme temperatures shall be planted; b. The selection of plants should be of such variety that their roots do not penetrate more than 30 cms. This condition shall apply till the landfill is stabilized; c. Selected plants shall have ability to thrive on low-nutrient soil with minimum nutrient addition; Plantation to be made in sufficient density to minimise soil erosion. d. Plantation to be made in sufficient density to minimise soil erosion. e. Special attention shall be given for green belt development. Green belts of broad leaf native species (non-edible) shall be developed in buffer zone of minimum 22-meter-wide area all around the boundary of the site. Project proponent shall develop green belt in at-least 33% area of total project area including the green belt mentioned in the buffer zone. Dense plantation shall be completed in first year before start of any activity at site related with solid waste management; failing which, environmental clearance may be cancelled.	Landfill is under operation stage. Will ensure post closure care after closing of landfills.
32	The post-closure care of landfill site shall be conducted for at least fifteen years and long term monitoring or care plan shall consist of the following, namely: a) Maintaining the integrity and effectiveness of final cover, making repairs and preventing run-on and run-off from eroding or otherwise damaging the final cover b)Monitoring leachate collection system in accordance with the requirement; c) Monitoring of ground water in and around landfill; d)Maintaining and operating the landfill gas collection system to meet the standards.	Landfill is under operation stage. Will ensure to comply this during post closure care after closing of landfills.
33	Use of closed landfill sites after fifteen years of post-closure monitoring can be considered for human settlement or otherwise only after ensuring that gaseous emission and leachate	Landfill is under operation stage. Will ensure use of closed landfill sites after fifteen years of post-closure monitoring for human settlement or otherwise only after ensuring that gaseous emission and leachate quality analysis





	quality analysis complies with the specified standards and the soil stability is ensured.	complies with the specified standards and ensuring the soil stability.
34	The incoming organic waste at site shall be stored properly prior to further processing. To the extent possible, the waste storage area should be covered. If, such storage is done in an open area, it shall be provided with impermeable base with facility for collection of leachate and surface water run-off into lined drains leading to a leachate treatment and disposal facility.	The incoming organic waste at site is stored on tipping floor properly prior for further processing.
35	Necessary precaution shall be taken to minimise nuisance of odour, flies, rodents, bird menace and fire hazard.	Daily covering with 15cm soil on landfill to prevent odors, birds etc. and fire hydrant installed. Odour control measures have been taken thrice in a weak, using odour control liquid spray on the waste storage at tipping floor. For proof ANNNEXURE- XIII has been attached.
36	In case of breakdown or maintenance of plant, waste intake shall be stopped and arrangements be worked out for diversion of waste to the temporary processing site or temporary landfill sites which will be again reprocessed when plant is in order.	We have sufficient machineries (Two 75 mm trammel) providing facilities of waste processing and adequate space (2200 sqm area for accommodating in coming waste of volume 5500 m^3 which implies to store in coming waste till two weeks) for storage of incoming waste at the time of breakdown and maintenance of the plant. So, we do not need to send the incoming waste to the temporary processing site or temporary landfill sites which will be again reprocessed when plant is in order.
37	Pre-process and post-process rejects shall be removed from the processing facility on regular basis and shall not be allowed to pile at the site. Recyclables shall be routed through appropriate vendors. The non-recyclable high calorific fractions to be segregated and used for RDF production. Only rejects from all processes shall be sent for sanitary landfill site(s).	Pre-process and post-process rejects are removed from the processing facility on regular basis and not allowed to pile at the site. Recyclables are routed through appropriate vendors which are authorized recyclers. The non-recyclable high calorific fractions are segregated and used for RDF production and sent to cement plants on regular basis. Only rejects from all processes are sent to sanitary landfill site(s) as inert.
38	The windrow area for composting shall be provided with impermeable base. Such a base shall be made of concrete or compacted clay of 50 cm thick having permeability coefficient less than 10–7 cm/sec. The base shall be provided with 1 to 2 per cent slope and circled by lined drains for collection of leachate or surface runoff.	The windrow area for composting is provided with impermeable base. Such a base is made of concrete and the base is provided with 1 to 2 per cent slope and circled by lined drains for collection of leachate or surface run-off.





39	Leachate shall be re-circulated in compost plant for moisture maintenance	Leachate is re-circulated in compost plant for moisture maintenance.
40	The end product compost shall meet the standards prescribed under FCO notified from time to time.	We test our compost as per F.C.O standards that so that compost quality meets the specifications prescribed in Solid Waste Management Rules, 2016 notified vide so 1357 (E) Dated 08/04/2016. Both Internal and external report has been mentioned in the ANNEXURE- XIV
41	Project proponent shall ensure that in order to ensure safe application of compost, compost quality shall be met the specifications prescribed in Solid Waste Management Rules, 2016 notified vide so 1357 (E) Dated 08/04/2016. Compost quality exceeding the above-mentioned standards shall not be used for food crops. However, it may be utilized for purposes other than growing food crops	We test our compost as per F.C.O standards that so that compost quality meets the specifications prescribed in Solid Waste Management Rules, 2016 notified vide so 1357 (E) Dated 08/04/2016.
42	Ambient air quality monitoring shall be regularly carried out. Odour nuisance at down-wind direction on the boundary of processing plant / landfill side shall also be checked regularly.	Ambient air quality monitoring is regularly carried out and that odour nuisance at downwind direction on the boundary of processing plant /landfill side is also checked regularly. Test reports are kept in record on periodic basis.
43	Project proponent shall provide 'adequate measuring arrangements for the measurement of water utilize in different categories and effluent generated. Good housekeeping practices shall be adopted	Being complied. For the measurement of water utilization separate flow meter has already been installed with bore well. Monthly, hourly monitoring data is recorded properly to prevent over consumption of limit mentioned in the ground water NOC. Good housekeeping practices are also being mentioned. Please refer to the ANNEXURE - XV
44	Provision shall be made for the housing of construction labour with all necessary infrastructure and facilities such as fuel for cooking (with proper safety arrangement), mobile toilets, mobile STP, safe drinking water, medical health care, crutch etc. The housing may be in the form of temporary structures to be removed after the completion of the project.	Complied during the time of plant construction. All the temporary structures removed after the full establishment of the project. No further construction has been taken place after the date mentioned in the CFE letter. During each landfill construction labours appointed for the same are provided the existing toilets, safe drinking water, medical health care facilities and all other necessary facilities as other employees present in the plant.





45	Project proponent shall take proper action to control the noise pollution. Project proponent shall install appropriate noise barriers /control measures including acoustic hoods, silencers, enclosures etc. on all sources of noise generation to control the noise. Earplugs/ear muffs etc. shall be provided to the employee working in the high noise areas (if any). Leq of /noise levels emanating from machines shall be limited to 75 dBA. The noise level shall not exceed the limits 75 dB (A) during the daytime and 70 dB (A) during the night time within the premises. Project proponent shall take adequate measures for control of noise level below 85 dB (A) in the work environment.	Noise level within plant premises is within range as per the standard by CPCB. ANNEXURE - XVI attached.
46	A separate environment management cell with full fledge laboratory facilities to carry out various management and monitoring functions shall be set up under the control of a Senior Executive.	Complied
47	Project proponent shall ensure compliance of all provisions of Solid Waste Management Rules. 2016 notified vide so 1357 (E) Dated 08/04/2016.	Complied
48	Transportation of waste by covered vehicles only shall be ensured. Provision for monitoring of vehicles by installation of close circuit cameras at suitable locations i.e. entry gate, weigh bridge etc. shall also be made	Transportation of waste is carried out by hydraulic compactors which are covered vehicle. Monitoring of vehicles by installation of close circuit cameras at suitable locations i.e., entry gate, weigh bridge etc. is in place.





49	Project proponent shall constitute a monitoring committee comprising of representatives of all stake holders i.e., Gram Panchayat. Villagers, workers, transporters and management etc. This committee shall monitor the environmental protection measures adopted, transportation of solid wastes. Complaints (if any) etc. The committee shall monitor the above matters atleast once in a two month: during which, factual situation regarding above matters will be discussed. Project proponent shall ensure meeting of this committee at regular interval. The proceedings of the committee shall be recorded in writing along with suggestions (if any). Project management shall take immediate action on the basis of observations / suggestions of the committee. A copy of the proceedings of the committee shall be submitted to Regional Officer, Chhattisgarh Environment Conservation Board, and Bilaspur for information.	Noted, we will comply before the submission of the next half yearly report for the tenure Oct- 24- Mar- 25.
50	Health camp shall be organised in Kachhar and nearby villages in every six months for health check-up of village people. Health check-up of workers shall be done every month regularly	Health Camp has already been Organised by DMSWSL on 5.09.23. Please refer to the ANNEXURE – XVII.
51	Project proponent shall ensure continuous operation of processing plant to prevent birds / fly / mosquito etc. nuisance. Preventive measure shall be ensured within and nearby areas of processing / landfill site for prevention and control of birds/ fly / mosquito etc. nuisance. Project proponent shall not mix and / or dispose anima' carcass, bio-medical wastes etc. in the processing / landfill site.	Continuous operation of processing plant is carried out to prevent birds / fly / mosquito etc. nuisance. Shed for the processing area and covering of landfill with 15cm soil on it is given as a preventive measure to control birds/flies/mosquitos etc. nuisance. We do not mix and / or dispose anima' carcass, biomedical wastes etc. in the processing / landfill site.





52	SEIAA. Chhattisgarh reserves the right to revoke the clearance if conditions stipulated are not implemented to the satisfaction. SEIAA. Chhattisgarh reserves the right to amend / cancel any of the conditions and add new conditions and make further stringent the emission / effluent limit as and when deemed necessary in the interest of environmental protection, change in the project profile or non-satisfactory implementation of the stipulated conditions etc.	Agreed
53	Project proponent shall advertise it at least two local newspapers widely circulated in the region around the project, one of which shall be in the vernacular language of the locality concerned within seven days from the website of SEIAA, Chhattisgarh at www.seiaac.org.	Complied
54	A copy of the clearance letter shall be sent by the proponent to concerned Panchayat, Zila Parishad / Municipal Corporation, Urban Local Body and the Local NGO, if any, from whom suggestions / representations, if any. Received while processing the proposal. The clearance letter shall also be put on the website of the project proponent.	Complied
55	Half yearly report on the status of implementation of the stipulated conditions and environment safeguards shall be submitted to the Chhattisgarh Environment Conservation Board Raipur, Regional Office, Chhattisgarh Environment Conservation Board, Bilaspur, SEIAA, Chhattisgarh and Regional Office, Ministry of Environment, Forest and Climate Change. Government of India. Nagpur	Submitted previously and will be submitted in future also.





56	Regional Office of the Ministry of Environment. Forest and Climate Change at Nagpur will monitor the implementation of the stipulated conditions. A complete set of documents including Environment Impact Assessment Report and Environment Management Plan along with the additional information submitted from time to time shall be forwarded to the Regional Office for their use during monitoring. Project proponent will upload the compliance status in their website and up-date the same from time to time at least six-monthly basis.	Complied and half yearly compliance report uploading process is under progress.
57	Full cooperation shall be extended to the Scientists / Officers from the SEIAA, Chhattisgarh, Ministry of Environment, Forest and Climate Change, Government of India /Regional Office, Ministry of Environment, Forest and Climate Change, Government of India. Nagpur I CPCB I Chhattisgarh Environment Conservation Board, who would be monitoring the compliance of environment status.	Complied
58	In case of any deviation or alteration in the proposed project from those submitted to this SEIAA, Chhattisgarh for clearance, a fresh reference should he made to the SEIAA, Chhattisgarh to assess the adequacy of the condition(s) imposed and to add additional environment protection measures required, if any. No further addition, expansion or modifications in the site / plant should be carried out without prior approval of the Ministry of Environment, Forest and Climate Change, Government of India / SEIAA, Chhattisgarh.	No deviation or alteration in the proposed project from those submitted has been taken place before receiving and till date from the receiving of EC. We are being complied all the conditions mentioned in the EC. No further addition, expansion or modifications in the site / plant has been executed.
59	Concealing factual data or submission of false / fabricated data and failure to comply with any of the conditions mentioned above may result in withdrawal of this clearance and attract action under the provisions of the Environment (Protection) Act, 1986.	Complied





60	The project authorities must strictly adhere to the stipulations made by the Chhattisgarh Environment Conservation Board (CECB) and the State Government.	Complied
61	The above stipulations would be enforced among others under the Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and Control of Pollution) Act. 1981. The Environment (Protection) Act, 1986 and rules made there under.	The above stipulations has been already enforced among others under the Water (Prevention and Control of Pollution) Act, 1974, the Air (Prevention and Control of Pollution) Act. 1981. The Environment (Protection) Act, 1986 and rules made there under.
62	The issuance of this environmental clearance does not convey any property rights in either real or personal property, or any exclusive privileges. Nor does not authorize any injury to private property or any invasion of personal rights, nor any infringement of Central, State or Local laws or regulations.	Complied
63	Any appeal against this environmental clearance shall lie with the National Green Tribunal, if preferred, within a period of 30 days as prescribed under section 16 of the National Green Tribunal Act, 2010.	Complied






ANNEXURE-I



LAND DOCUMENT



Pre- Feasibility Report

राज्य स्तर विशेषज्ञ मूल्यांकन समिति, छत्तीसगढ भारत सरकार पर्यावरण, वन एवं जलवायु परिवर्तन मंत्रालय — 00 :— प्रथलेशन विश्वपार्यान कृपया आपके पत्र दिनांक 25/04/2016 एवं 13/06/2016 का अवलोकन हो। औनस्वार्षित आवेदन प्राप्तिः दिस्तांक — यह आवेदन दिगांक 24/12/2015 से द्वारा जीनस्वार्षित पद परियोगां प्राप्तांक द्वारा विशांक 11/04/2016 की प्राप्त हुआ है। प्राप्तीयक स्थान्य - एचावार्षित्र (मोदी / एचावार्षित्र) निर्माण हुआ है। प्राप्तीयक स्थान्य - एचावार्षित्र (मोदी / एचावार्षित्र) निर्माण हुआ है। प्राप्तीयक्षण का स्थान - भेक्सने स्थार प्राप्तिक निरमा, विस्तासुर (कीमन पुनितिस्तर सीतिक संदर निर्माण विशित्स) परियोजना का पता — खत्तरा मं. 1359 एवं 1052, ग्राम-कंछार, तहसील व जिला-विलासपुर • भूमि का क्षेत्रफल — 10 हेक्टेयर

CHAPTER 7- RISK ASSESSMENT AND DISASTER MANAGEMENT PLAN IN THE COMMON MUNICIPAL SOLID WASTE MANAGEMENT PROJECT

Risk Assessment Report






SEAC Letter





ANNEXURE -II





Agreement for 15 years with BMC (Bilaspur Municipal Corporation)





Landfill Cell B in Operation





Landfill Cell A completed.





ANNEXURE -III



भारतीय विमानपत्तन प्राधिकरण AIRPORTS AUTHORITY OF INDIA

BILASPUR MUNICIPAL CORPORATION, EXECUTIVE ENGINEER, MR. ANUPAM TIWADate: 24-03-2022

VIKAS BHAWAN , NEHRU CHOWK, BILASPUR, CHHATTISGARH, 495001

System Generated Auto Assessment for Height Clearance

- Airports Authority of India (AAI) in pursuance of responsibility conferred by and as per the provisions of Govt. of India (Ministry of Civil Aviation) order GSR 751 (E) dated 30th Sep. 2015 for Safe and Regular Aircraft Operations has assessed the site data filled by the applicant.
- 2. Assessment details for Height Clearance:

NOC ID :	BILA/EAST/B/030622/658950
Applicant Name*	Anupam Tiwari
Site Address*	DELHI MSW SOLUTIONS LIMITED (MUNICIPAL SOLID WASTE MANAGEMENT PROJECT) LOCATED AT KACHHAR, 495009 SURVEY NOS – 1359, 1052/1 SENDRI KACHHAR VILLAGE BILASPUR TALUK BILASPUR DISTRICT CHHATTISGARH STATE
Site Coordinates*	22 10 45.50N 82 06 43.68E, 22 10 53.63N 82 06 50.58E, 22 10 41.14N 82 06 50.68E, 22 10 57.41N 82 06 55.18E, 22 10 43.98N 82 06 55.98E, 22 10 40.50N 82 06 57.41E, 22 10 40.12N 82 06 58.05E, 22 10 48.36N 82 06 58.59E, 22 10 42.12N 82 06 59.84E
Site Elevation in mtrs AMSL as ubmitted by Applicant*	284.98 M
Type Of Structure*	Waste Management Facility

^{*}As provided by applicant

Your site is located at a distance 20438 mts from ARP and lies in the grid A12 of the published CCZM of Bilaspur airport. The Permitted top elevation for this grid is 416 mts.

Since the requested top elevation 309.98 mts in AMSL is below CCZM permitted top elevation, the NOC for height clearance is not required from Airports Authority of India.

- 3. This assessment is subject to the terms and conditions as given below:
- a. The site-elevation and site coordinates provided by the applicant are taken for calculation of the permissible top elevation for the proposed structure. If however, at any stage it is established that the actual data is different from the one provided by the applicant, this assessment will become invalid.
- b. The Site coordinates as provided by the applicant in the NOC application has been plotted on the street view map and satellite map as shown in ANNEXURE. Applicant/Owner to ensure that the plotted coordinates corresponds to his/her site.In case of any discrepancy,this assessment shall be treated as null and void
- c. Airport operator or his designated representative may visit the site (with prior coordination with applicant or owner) to ensure that assessment terms & conditions are complied with.
- d. The assessment is further subject to the provisions of Section 9-A of the Indian Aircraft Act, 1934 and any notifications issued there under from time to time including the Aircraft(Demolition of Obstruction caused by Buildings and Trees etc.) Rules, 1994.


राजीव गांधी भवन Baiy Gandhi Bhawan लफदरवंग हवाई अड्डा नई दिल्ली—110003 Safdarjung Airport, New Delhi-110003 युरमाष : 24632950


NOC from AAI (Airport authority of India)






ANNEXURE -IV







The facility area for landfill, processing and disposal of solid wastes has already been incorporated in the Town Planning Department's land-use plan.





ANNEXURE -V



Figure 4.7: Featured around 500 m from the project site

500 m Buffer around the project site is maintained





ANNEXURE -VI







Main gate & Boundary Wall





ANNEXURE -VII





Separate sanitary facilities for washing and bathing for workers are provided. Drinking water facilities is provided by a separate water filter of drinking water





ANNEXURE -VIII

roje	t Code						м	E LOG SHEET		Sh			Date	14-/11/2		
1	1			VS		VS-I		ME		CHARACH	SDENSATE STERISTICS		4	STEAST	SOLID	SEPERATOR
SL SO	TIME(HIS)	FEED TO MEE(M'/400)	STEAM PRESSURE TO EVAPORATOR(KG/CM ²)	VACCUMER MM HG)	TEMP C	VACCUME(MM HG)	TEMP C	CONCENTRATE SPECIFIC GRAVITY	CONDENSATE FLOW(M*HR)	TDS	PH	FEED TO ATFD (KGHR)	FEED PH	PRESSURE TO ATED (NG/CM ³)	OUTPUT (KG/HR)	TEMP
21	9:25	0.747	3 - 6	489	71.3	543	637		0.574	9742	8.87	165		3.2	61.7	
02	10:25	0 735	3.7	493	742	547	66.2		0.568	818-7	8.74	168		3.3	62.5	
03	11:25	0.739	3.3	497	77-5	550	66.8		0.544	707-3	8-65	169		3-4	630	
04	12:25	0.74	3.2	499	79.1	548	67.9		0.552	621-6	8.53	171		3-1	60.0	
05	13:25	0.741	3.5	482	81.3	549	69.4		0.563	5R.8	8.37	163		3.6	60.7	
06	14:25	0.74	3.8	485	835	537	61.6		0.572	434.9	8.18	167		3.7	61-9	
07	15:25	0.74	3.0	492	83.7	544	64.3		0.553	323.5	7.96	169		3.5	63.3	
08	16:25	0.74	3.1	495	84.8	546	66.4		0.547	268-7	7.81	168		3.0	65.1	
09	17:25	0.737	3.4	500	82.6	549	67.3		0.551	189.6	7.43	170		3.3	62.8	
10	18:25	0.79	3.6	497	83.9	547	68.5	5	0.565	123.3	7.29	164		3.5	62.0	
					-			-	-						-	-
4				-	-		-	-	-				-		-	-
4				-	-		-	1				-	-		1	-
				-	-		-	1	-	-			1		+	1
4				-	-	-	-			-			1	-	1	-
		/ 14														
		Coule	HARGE					nning						PLANT HEAD		

Sustainabil	ify					ME	E LOG SHEET		Sh					Date	14.11.
			VS-I		VS-II MEE					DENSATE FERISTICS			CYCLONE		
TIME(HRS		STEAM PRESSURE TO EVAPORATOR(KG/CM²)	VACCUMEC	гемр с	VACCUME(MM-HG)		CONCENTRATE SPECIFIC	CONDENSATE FLOW(M³/HR)	TDS	РН	FEED TO ATFD (KG/HR)	FEED PH	PRESSURE TO ATFD (KG/CM ²)	SOLID OUTPUT (KG/HR)	Т
1 9:10	0.739	3.7	491	83.9	546	65.7		0.577	1011.6	8.95	168		3.3	61.6	
2 10 10	0.742	3.5	493	82.7	543	67.6		0.568	989.7	8.74	167		3.5	62.4	
3 11- 1	0 0.746	3.6	497	81-5	547	69.4		0.567	873.6	8.69	169		3.4	62.9	
4 12 1	0 0.741	3.3	496	82-3	544	66.8		0.571	709.3	8.53	166		3.7	61.8	
5 13:1	0 0.74	3.1	492	83.5	545	67.6		0.553	653.8	8.31	165		3.6	62.3	
06 14:	0 0.73	3.4	489	84.3	548	68.9		0.563			170		3.3	62.7	
07 15:	10 0.73		493	82.6	541	-		0.553			164		3.1	62.5	
08 16 .	10 0.74		495					0.565			167		3.4	60.9	
	10 0.74		497			65.		0.573					3.7	61.6	
10 18	10 0.74	-3 3.7	444	14.	1 54										
	/50	LANCHARGE					unning feed						PLANT HEAD		

Multi Effective Evaporator to meet the prescribed standards and treated effluent is used for watering the plantation around the plant premises. We follow ZLD in our plant premises





ANNEXURE -IX





Figure: 4.11: Sampling locations marked on Google earth




Ground water quality monitoring and reporting is conducted by a NABL certified lab within 50 meter of the periphery of site on periodic basis covering different seasons in a year that is, summer, monsoon and post-monsoon period to ensure that the ground water is not contaminated.





<u>ANNEXURE –X</u>






Ground water assessment report from NABL certified LAB to ensure the quality of the water.





ANNEXURE -XI




air monitoring from NABL certified lab which shows that the concentration of methane gas generated at landfill site does not exceed 25 per cent of the lower explosive limit [LEL].





<u> ANNEXURE –XII</u>





Test reports are kept in record on periodic basis. Periodic monitoring report of ambient air quality monitoring




Covering with 15cm soil on landfill to prevent odours, birds etc.





ANNEXURE -XIII





Odour control measures have been taken thrice in a weak, using odour control liquid spray.





Figure: 4.11: Sampling locations marked on Google earth





ANNEXURE -XIV





Internal test report of city compost as per the FCO guideline

External test report of city compost as per the FCO guideline





ANNEXURE -XV

Date	Totalizer(m³)	
01/12/2024	3.94	
02/12/2024	5.53	
03/12/2024	0.97	
04/12/2024	2.79	
05/12/2024	0.81	
06/12/2024	1.22	
07/12/2024	1.17	
08/12/2024	3.59	
09/12/2024	1.08	
10/12/2024	1.09	
11/12/2024	0.85	
12/12/2024	0.97	
13/12/2024	0.28	
14/12/2024	0.47	
15/12/2024	0.97	
16/12/2024	0.49	
17/12/2024	0.36	
18/12/2024	0.91	
19/12/2024	0.48	
20/12/2024	0.58	
21/12/2024	0.41	
22/12/2024	0.85	
23/12/2024	0.06	






			(0.55)	60 day ordi				River D Ce	ज जल र और केन्द्रीय Gove Minis partmen evelopm	भारत सरक ल शक्ति मं इंसाधन, नर्द गंगा संरक्षण त भूमि जल ह ernment c stry of Ja tof Wate eent & Ga ound Wa	त्रालय विकास विभाग प्राचिकरण of India I Shakti er Resou anga Rei	iuver	
NO	OBJE	CTION CER	TIFICA	निकासी हे FE (NOC	तु अन :) FO	R GRO	IUI UA)	WATER	ABS	TRAC	TION		
Project Name:			Establish	ment For	Storaç	ge Transp	oort Se	peration [*]	Treatme	ent And	Dispos	al	
Project Addres	ss:			nent Of Co Village, S			the state of the s						
Village:	Kachhar	Block:	Belh	a									
District:	Bilaspur	State:			tisgarh								
Pin Code:						0.111	Linogai						
Address of Co			Bilaspur, Central C	I Corporat Chhattisg Bround Wa stic Park,	arh - 4 ater Bo	95001 pard Nort	h Centr	al Chhati	tisgarh,	2nd Flo	or, Lk C	Corp	
1. NOC No.:		CGWA/NOC	/IND/REN/	Date of Issuence			16/11/2023						
3. Application	No.:	21-4/3843/C	T/IND/202	0	4.	Category: (GWRE 2022)		S	Semi Critical				
5. Project Sta	tus:	Existing Grou	und Water			6.	NOC Type: Valid up to:			Renewal 29/10/2026			
7. Valid from		30/10/2023				8.							
		raction Permit											
Fresh \			Saline W		watering			Total		1/1.10			
m³/day 10.00	m³/ye 3650.	.00		m³/year		m³/day	,	n³/year	m	³/day	m	³/yea	
10. Details of g	round w	ater abstractio		ring struct	tures			70	tal Da	annad N	10:0		
n c		Total Exist		w Tw	MP	MPu	DW	DCB	BW	osed N	MP	N	
Abstraction	Structur			1 0	0	0	0	0	0	0	0		
*DW- Dug Well; DC													
11. Ground Wa									219	00.00			
								0.00					

Monthly monitoring data is recorded properly to prevent over consumption of limit mentioned in the ground water NOC.





ANNEXURE -XVI



Noise level within plant premises is within range as per the standard by CPCB.





ANNEXURE –XVII







